ACTIVE SPLITTER - CATV

1 INPUT - 8 OUTPUT



Features

- Up to 512 QAM Support
- Very Good Isolation
- Balanced Output
- Excellent Uniformity

Specification

Input level : 85dBuV / Channel (Max)
Band Width : 45 Mhz to 1000Mhz
Gain : ± 1dB
Output IP1 : 25 dBm
Output IP3 : 42 dBm
Linearity : ± 1.5dB
Noise Figure : < 2.5 dB
Isolation : >23 dB
No of Input : One
No of Output : Eight
Connector : F Type 75 Ohm

Electrical

Input Voltage : 12 VDC
Power Consumption : 3 Watt

Application

- FM Radio
- Terrestrial Antenna
- CATV DHE
- VHF & UHF Antenna

Mechanical

Type : Indoor
Enclosure : Aluminium
Mounting : 1U Rack Mounting
Top : -10 to 55 Dec C
DC Jack : 2 mm X 5.5mm
Dimension : 490mm X 200mm X 50mm(LBH)
Weight : 3Kg

Packaging Contents:

Active Splitter - 1No
Adopter - 1No

Ordering Information

Model No : AHSA-08F - 75 Ohm F Female

AMPTRONIX
1st,Floor,No36/32,Sriram Nagar Main Road, Pallipattu, Taramani,
Chennai,Tamil Nadu,INDIA. Postcode: 600113
Mobile: 0 94459 56787
www.amptronix.co.in Email. sales@amptronix.co.in

Notes