L BAND SPLITTER - ACTIVE

1 INPUT - 8 OUTPUT





Features

- Low Noise
- Zero Phase
- Excellent Uniformity
- High IP3
- 1U Rack Mount

Specification

Input level : 75dBuV / Channel (Max)
Band Width : 900 to 2150Mhz
Gain : ± 2dB
Output P1 : 11dBm
Output IP3 : 25dBm
Linearity : ± 1.5dB
Noise Figure : < 3.5 dB
Isolation : >22 dB
No of Input : One
No of Output : Eight
Connector : BNC & SMA - 50 Ohm
: F - 75 Ohm

Electrical

Input Voltage : 18VDC
Power Consumption : 4Watt @ 18VDC

LNB Power

Type : Manual On/Off
Voltage : 18 VDC
Current : 0.5 A max

Application

- GPS
- C Band Downlink
- Ku Band Down Link
- CATV Digital Head End
- UHF Antenna Signal
- DUT Testing

Mechanical

Type : Indoor
Enclosure : Aluminium
Mounting : 1U Rack Mounting
Top : -10 to 55 Dec C
DC Jack : 2 mm X 5.5mm
Dimension : 490mm X 200mm X 50mm(LBH)
Weight : 3Kg

Packaging Contents:

L Band IF Splitter - 1No
Adopter - 1No

Ordering Information

Model No : ALSA-08B - 50 Ohm BNC Female
: ALSA-08S - 50 Ohm SMA Female
: ALSA-08F - 75 Ohm F Female

AMPTRONIX
1st,Floor,No36/32,Sriram Nagar Main Road, Pallipattu, Taramani,
Chennai,Tamil Nadu,INDIA. Postcode: 600113
Mobile: 0 94459 56787
www.amptronix.co.in Email. sales@amptronix.co.in

Notes